



Daylight Harvesting Controls

Luxstat Wall Switches

KEY FEATURES

- Provides manual control of Luxstat Daylight Harvesting Control Modules
- Automatic mode LED indicator (4-button version)
- Manual mode LED indicator (4-button version)
- Manual dimming (4-button version)
- Manual ON/OFF switching
- Low voltage operation; Class 2 device
- Architecturally attractive design
- California Title 24 compliant
- UL and cUL listed
- 5-Year Warranty



OVERVIEW

The Luxstat 4-Button Wall Switch by Servodan allows occupants to override automatic daylight control. The Luxstat 4-Button Control Station has four buttons and two LED indicators. One LED indicates the lights are being manually overridden and the other that they are being controlled automatically. Pressing the I/O button puts the controller into manual mode and switches the lights on or off. Pressing and holding the up or down button increases or decreases light level. All three channels are dimmed or switched in unison. The Auto button switches the controller into automatic operation.

SPECIFICATIONS

Electrical	<ul style="list-style-type: none"> • Low voltage, class 2 device • Maximum wire length from controller is 150 feet (45.72m)
Dimensions	<ul style="list-style-type: none"> • 4-button Switch - 4.88" x 3.13" x .38" (124mm x 80mm x 10mm) LxWxD • 1-button Switch - 2.6" x 2.6" (66mm x 66mm)
Certifications	<ul style="list-style-type: none"> • UL and cUL listed
Warranty	<ul style="list-style-type: none"> • Five-year warranty

HOW TO ORDER

Catalog Number	Description
LUXSTATSW4	Luxstat 4-Button Wall Switch
LUXSTATSWI	Luxstat 1-Button Momentary Switch