



## LX Series Networked Lighting Controls Series

### Sentry Switch Remote Line Voltage Light Switch with Local Override

#### KEY FEATURES

- Standard wall switch ON/OFF operation
- Toggle or Decorator style
- Mechanically switches to OFF position when power is interrupted for 5 seconds
- Locator light illuminates switch when lights are off
- UL and cUL listed
- Switches operate between specific load ranges listed below



#### OVERVIEW

The Sentry Switch™ allows individual override control of local line-voltage circuits when used with the scheduling features of the LX Networked Lighting Control Panel. When the panel relay is ON and the circuit is powered, the switch functions normally and can manually turn lights on and off. However, when the panel is scheduled to turn the lighting off, a programmed 5-second OFF signal will cause the switch to mechanically go to the OFF position. After this time, power returns to the circuit, and the switch functions normally. This unique product allows the panel to sweep the lights OFF in multiple areas while maintaining the normal operation of the switch. When used with the LX Lighting Control Panel, the Sentry Switch provides a very economical means of controlling multiple areas with a single dedicated relay on the LX panel.

#### FEATURES and BENEFITS

Features	Benefits
Load requirements	<ul style="list-style-type: none"> <li>• LXS05—0.2A minimum; 5.0A maximum</li> <li>• LXS20—1.0A minimum; 20.0A maximum</li> </ul>
Power requirement	<ul style="list-style-type: none"> <li>• 120, 240, or 277 VAC</li> <li>• No neutral required</li> </ul>
Connections	<ul style="list-style-type: none"> <li>• 2-wire connection; SPST</li> <li>• 3-wire connection; SPDT—three-way</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>• UL and cUL listed</li> </ul>
Mounting	<ul style="list-style-type: none"> <li>• Single-gang NEMA style switch box</li> <li>• Standard or Decorator style wall plate (not included)</li> </ul>
Warranty	<ul style="list-style-type: none"> <li>• 5 years</li> </ul>

#### HOW TO ORDER

Catalog Number	Rating	Style/Color
LXS05T	5A 120/240/277VAC	Toggle
LXS05DW	5A 120/240/277VAC	Decorator-White
LXS05DI	5A 120/240/277VAC	Decorator-Ivory
LXS05T3	5A 120/240/277VAC	Three-Way Toggle
LXS05T3W	5A 120/240/277VAC	Three-Way Decorator-White
LXS05T3I	5A 120/240/277VAC	Three-Way Decorator-Ivory
LXS20T	20A 120/240/277VAC	Toggle
LXS20DW	20A 120/240/277VAC	Decorator-White
LXS20DI	20A 120/240/277VAC	Decorator-Ivory
LXS20T3	20A 120/240/277VAC	Three-Way Toggle
LXS20T3W	20A 120/240/277VAC	Three-Way Decorator-White
LXS20T3I	20A 120/240/277VAC	Three-Way Decorator-Ivory