



Ceiling and Wall Mount Occupancy Sensors *Occupancy Sensor Accessories*

ACAK — ACOUSTIC CEILING MOUNTING KIT

for ceiling and wall mount sensors used with acoustic ceiling tile. ACAK uses integral cutting teeth for quicker installation. Color: White.



LMRA — LIGHTOWL MUD RING ADAPTER

A LightOWL goof ring for covering oversized holes. Color: White.



HCRA — HARD CEILING RACEWAY ADAPTER

for OMNI™ sensors. The HCRA is compatible with Hubbell™ and Wiremold™ raceway. The HCRA has knockout raceway holes for quick and clean installation. Color: White.



OPE — OMNI Protective Enclosure

The OPE is a NEMA Type 4X enclosure specifically designed for use with HBA's OMNIIR ceiling mount occupancy sensor. Designed to provide protection from foreign materials and water, the enclosure is acceptable for use in a variety of environments including applications in the pharmaceutical and food preparation industries. Size: 6.5" dia., 2" height. Color: White.



WGWS – Wall mount wire guard for wall switches, 6.25"H x 4.0"W x 2.25"D

WGLO – Wall mount wire guard for LightOWL sensors, 7.0"H x 5.75"W x 4.5"D

WGOMNI – Ceiling mount guard for OMNI sensors, 7.0"W x 3.25"D (circular guard)

Wire guards are heavy-duty coated wire guards for sensors to protect from destructive strikes. Mounting clips are included. Color: White.

